

Datum: 17.12.2025



Piston rod-free cylinder ZRL1C, Ø 40, Stroke 1600, Standard

(slika je simbolična)

Kategorija: [Rodless cylinders ZRLC](#)

Šifra: **129859RIE**

Kratek opis

Piston rod-free cylinder ZRL1C, Ø 40, Stroke 1600, Standard, Working pressure 0,5 - 8 bar, Temp. -10 to 80 °C
Rodless cylinder in classic design with high carriage. Please refer to our type code for the available variants and their corresponding type designations for your individual inquiry. Other special designs are also available on request
The integrated sliding guide allows higher loads and makes the cylinders less sensitive to moisture, dirt and shocks.
Suitable for filtered (50 µm) and unlubricated or lubricated compressed air. Please ensure continuous oiling when using oiled compressed air.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Cushioning	cushioned
Ffunkcija	double-acting
Magnet	with magnet
Piston caps and sliding parts	abrasion-resistant plastic
Povezava	G 1 /4
Sealing bands	Stainless steel
Tesnilo	Oil proof synthetic material (NBR)
Min. delovni tlak [bar]	0.5
Max. delovni tlak [bar]	8
Bat Ø [mm]	40
Max. temperaturno območje [°C]	80
Stroke [mm]	1600