

Datum: 29.04.2025



(slika je simbolična)

Plošč.ventil HDM prik.4 mm 2x3/2NC mono ali 5/3 sredina odzračena

Kategorija: [Valve disc for HDM valve terminal with 4 mm port](#)

Šifra: **106674RIE**

Kratek opis

Valve disc for valve terminal HDM, Connection 4 mm, 2x 3/2-way, NC, monostable or 5/3-way, Centre vented
These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.
Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Monostable (non-latching) version of manual control also available on request.
The operating pressure is based on the installed input plates.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
IP zaščita	IP 65
Material	aluminium
Poskusno	Max. 16 (e.g. 16 spring return valves)
Ročno upravljanje	latching
Vhodna moč	0.6 W per pilot 2x 3/2-way, NC, monostable or 5/3-way, centre vented
Ffunkcija	
Max. temperaturno območje [°C]	60
Pretok [NI/min]	200