

Datum: 30.04.2025



(slika je simbolična)

## Ploščati ventil HDM priključek 4 mm 5/2-potni monostabilen

Kategorija: [Valve disc for HDM valve terminal with 4 mm port](#)

Šifra: **106677RIE**

### Kratek opis

Valve disc for valve terminal HDM, Connection 4 mm, 5/2-way, monostable, Temp. -10 °C to 60 °C

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates.

Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Monostable (non-latching) version of manual control also available on request.

The operating pressure is based on the installed input plates.

### Tehnične Specifikacije

|                                |                                        |
|--------------------------------|----------------------------------------|
| Min. temperaturno območje [°C] | -10                                    |
| IP zaščita                     | IP 65                                  |
| Material                       | aluminium                              |
| Poskusno                       | Max. 16 (e.g. 16 spring return valves) |
| Ročno upravljanje              | latching                               |
| Vhodna moč                     | 0.6 W per pilot                        |
| Ffunkcija                      | 5/2-way, monostable                    |
| Max. temperaturno območje [°C] | 60                                     |
| Pretok [NI/min]                | 200                                    |