

Datum: 30.04.2025



(slika je simbolična)

## Pnevmatsko gnani zaporni ventil, G 1/2, Čep connector 12/4

Kategorija: [Stop valve, ports 2 and 3 with plug connection](#)

Šifra: **107068RIE**

### Kratek opis

Stopper valve pneumatically actuated, G1/2, Plug connector 12/4, Working pressure max. 10bar, Medium / ambient temp. -10°C to 70°C

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Note: Pilot pressure is depending on operating pressure.

### Tehnične Specifikacije

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Min. sobna temperatura [°C]  | -10                                                          |
| Min. temperatura medija [°C] | -10                                                          |
| Material                     | Nickel-plated brass                                          |
| Port 1                       | G 1/2                                                        |
| Tesnilo                      | NBR                                                          |
| Vgradni položaj              | Any, ring piece can be rotated 360° after tighten. the valve |
| Min. vodeni tlak [bar]       | 1                                                            |
| Port 3                       | 4 mm                                                         |
| Max. vodeni tlak [bar]       | 5                                                            |
| Max. obratovalni tlak [bar]  | 10                                                           |
| Port 2                       | 12 mm                                                        |
| C [mm]                       | 41.0                                                         |
| Max. sobna temperatura [°C]  | 70                                                           |
| Max. temperatura medija [°C] | 70                                                           |
| B [mm]                       | 72.0                                                         |