

Datum: 01.05.2025



(slika je simbolična)

Pnevmatsko gnani zaporni ventil, G 1/4, Čep connector 6/4

Kategorija: [Stop valve, ports 2 and 3 with plug connection](#)

Šifra: **107066RIE**

Kratek opis

Stopper valve pneumatically actuated, G1/4, Plug connector 6/4, Working pressure max. 10 bar, Medium / ambient temp. -10°C to 70°C

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Note: Pilot pressure is depending on operating pressure.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Material	Nickel-plated brass
Port 1	G 1/4
Tesnilo	NBR
Vgradni položaj	Any, ring piece can be rotated 360° after tighten. the valve
Min. vodeni tlak [bar]	1
Port 3	4 mm
Max. vodeni tlak [bar]	5
Port 2	6 mm
Max. obratovalni tlak [bar]	10
C [mm]	28.0
B [mm]	58.0
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70