

Datum: 30.04.2025



(slika je simbolična)

## Polyethylene hose, Hose Ø 16x2 mm, natur, Roll of 25 m

Kategorija: [Polyethylene hose - LD-PE](#)

Šifra: **194274RIE**

### Kratek opis

Polyethylene hose (LD-PE), Temperature -40 °C to 60 °C, Hose Ø 16x2 mm, PN at 23 °C max. 7 bar, natural (milky), Roll of 25 m

Low-priced, calibrated hose for use with screw fittings. With its soft and flexible character, combined with relatively high strengths and good resistance to stress cracking, this hose is ideal for use in the following types of application:

- Flexible pneumatic lines in the low-pressure range, providing no special resistance to greases, oils or other hydrocarbons is required.
- Compressed air control lines.
- Vacuum lines (suitable for vacuum up to 10 x 8 mm).
- Supply lines of all kinds.

### Tehnične Specifikacije

|                                        |                      |
|----------------------------------------|----------------------|
| Min. temperaturno območje [°C]         | -40                  |
| Barva                                  | natural              |
| Material                               | Polyethylene (LD-PE) |
| Debelina stene [mm]                    | 2                    |
| Max. obratovalni tlak pri 23 ° C [bar] | 7                    |
| I.D. cevi [mm]                         | 12                   |
| O.D. cevi [mm]                         | 16                   |
| Dolžina koluta [m]                     | 25                   |
| Max. temperaturno območje [°C]         | 60                   |