

Datum: 29.04.2025



(slika je simbolična)

## **Predfilter »FUTURA-mali« Kov. pos. 0.3 µm, Vel. 0, G 1/4**

Kategorija: [Pre-filter with metal bowl](#)

Šifra: **142446RIE**

### **Kratek opis**

Pre-filter »FUTURA-mini« with metal container, 0.3 µm, Size 0, G 1/4, PE 1.5 - 12 bar, Temp. -10 °C to 50 °C, Semi-automatic

Pre-filters in modern design for compliance with strict compressed air purity requirements.

Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

### **Tehnične Specifikacije**

|                                |                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                                           |
| Element filtra                 | Impregnated paper<br>At P <sub>2</sub> = 6 bar and<br>pressure drop Δ <sub>p</sub> = 0.02 bar |
| Merjenje pretoka               | G 1/4                                                                                         |
| Navoj                          | Semi-automatic                                                                                |
| Odtok kondenzata               | PA66 GF60                                                                                     |
| Ohišje                         | Metal container                                                                               |
| Posoda                         | Plastic                                                                                       |
| Priključni navoj               | FUTURA-mini                                                                                   |
| Serijska                       | Compressed air, neutral gases                                                                 |
| Srednje                        | NBR                                                                                           |
| Tesnilo                        | 0.3                                                                                           |
| Rang filtra [µm]               | 1.5                                                                                           |
| Min. vhodni tlak [bar]         | 12                                                                                            |
| Max. vhodni tlak [bar]         | 27.0                                                                                          |
| C [mm]                         | 43.0                                                                                          |
| A [mm]                         | 50                                                                                            |
| Max. temperaturno območje [°C] | 132.0                                                                                         |
| B [mm]                         | 140                                                                                           |
| Pretok [l/min]                 |                                                                                               |