

Datum: 15.12.2025



(slika je simbolična)

## Predfilter»FUTURA«PC zbir.0.3 µmVel.1,G 1/4Pol avto.

Kategorija: [Pre-filter with polycarbonate bowl and bowl guard](#)

Šifra: **100157RIE**

### Kratek opis

Pre-filter »FUTURA« with PC container and protective cage, 0.3 µm, Size 1, G 1/4, 1.5-16 bar, Temp. -10°C to 50°C, Semi-automatic  
Pre-filters in modern design for compliance with strict compressed air purity requirements.  
Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

### Tehnične Specifikacije

|                                |                                                                                               |
|--------------------------------|-----------------------------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                                           |
| Element filtra                 | Impregnated paper<br>At P <sub>2</sub> = 6 bar and<br>pressure drop Δ <sub>p</sub> = 0.02 bar |
| Merjenje pretoka               | G 1/4                                                                                         |
| Navoj                          | Semi-automatic                                                                                |
| Odtok kondenzata               | PA66 GF60                                                                                     |
| Ohišje                         | Polycarbonate container<br>with protective cage                                               |
| Posoda                         | Material: Die-cast zinc                                                                       |
| Priključni navoj               | FUTURA                                                                                        |
| Serijska                       | Compressed air, neutral gases                                                                 |
| Srednje                        | 0.3                                                                                           |
| Rang filtra [µm]               | 1                                                                                             |
| Velikost                       | 1.5                                                                                           |
| Min. vhodni tlak [bar]         | 16                                                                                            |
| Max. vhodni tlak [bar]         | 39.5                                                                                          |
| C [mm]                         | 50                                                                                            |
| Max. temperaturno območje [°C] | 52.0                                                                                          |
| A [mm]                         | 169.5                                                                                         |
| B [mm]                         | 300                                                                                           |
| Pretok [l/min]                 |                                                                                               |