

Datum: 15.12.2025



(slika je simbolična)

Predfiltrirajte z diferenčnim manometrom, 3 µm, G 1

Kategorija: [Pre-filter with differential pressure gauge](#)

Šifra: **101548RIE**

Kratek opis

Pre-filter with differential pressure gauge, 3 µm, G 1, Input pressure 4 - 12 bar, Medium / ambient temperature 5 °C to 60 °C

For filtering out solid impurities larger than 3 µm and for moisture separation.

For connection upstream of a micro-filter or a combination micro-filter/activated carbon filter.

Tehnične Specifikacije

Element filtra	Polyethylene (with 45% cavity)
Ločevanje delcev [µm]	from 3
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 0.5\%$
Navoj	G 1
Ohišje	Aluminium
Posoda filtra	Aluminium
Max. označeni razpon diferenčnega manometra [bar]	2
Rang filtra [µm]	3
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	12
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	72.0
Učinkovitost [%]	99.99
A [mm]	118.0
B2 [mm]	420.0
D [mm]	458.0
B1 [mm]	517.5
Pretok [l/min]	3000