

Datum: 15.12.2025

**Prekl. ventil (3/2-smerni) »multifix«110 V AC Vel. 3G 1/2**

(slika je simbolična)

Kategorija: [On-off valves \(3/2-way valves\)](#)Šifra: **100623RIE****Kratek opis**

Switch valve (3/2-way valve) »multifix«, 110 V AC, 50 Hz, Size 3, G 1/2, Input pressure 2 - 10 bar, Med. / ambient temp. max. 60°C

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.

3/2-way type including silencer.

When they are switched off, the system is relieved at the same time.

Tehnične Specifikacije

Električni priključek	Device plug PG 9, type B, EN 175301-803
IP zaščita	IP65 (P 54) acc. to DIN 40050
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odzračevalni vtič	G 1/4
Ohišje	Die-cast zinc
Serijska	multifix
Tesnilo	NBR
Min. vhodni tlak [bar]	2
Velikost	3
Max. vhodni tlak [bar]	10
D [mm]	33.5
E [mm]	44.1
C [mm]	56.2
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	68.8
Delovni cikel [%]	100
Solenoid	110 V AC, 50 Hz
B [mm]	185.0
Pretok [l/min]	3150