

Datum: 29.04.2025

**Prekl. ventil (3/2-smerni) »multifix«110 V AC Vel. 4G 1**

(slika je simbolična)

Kategorija: [On-off valves \(3/2-way valves\)](#)Šifra: **133141RIE****Kratek opis**

Switch valve (3/2-way valve) »multifix«, 110 V AC, 50 Hz,
Size 4, G 1, Input pressure 2 - 16 bar, Med. / ambient temp.
max. 60 °C

Pneumatic systems or parts of systems can be switched on
and off by means of an electrical signal.

3/2-way type including silencer.

When they are switched off, the system is relieved at the
same time.

Tehnične Specifikacije

Električni priključek	Device plug PG 9, type B, EN 175301-803
IP zaščita	IP65 (P 54) acc. to DIN 40050
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Odzračevalni vtič	G 1/2
Ohišje	Die-cast aluminium
Serijska	multifix
Tesnilo	NBR
Min. vhodni tlak [bar]	2
Velikost	4
Max. vhodni tlak [bar]	16
E [mm]	35.0
C [mm]	53.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	66.0
A [mm]	85.0
Delovni cikel [%]	100
Solenoid	110 V AC, 50 Hz
B [mm]	204.0
Pretok [l/min]	12500