

Datum: 17.12.2025



(slika je simbolična)

**Prekl. ventil (3/2-smerni) »multifix«230 V AC Vel.4,G 3/4**Kategorija: [On-off valves \(3/2-way valves\)](#)Šifra: **133136RIE****Kratek opis**

Switch valve (3/2-way valve) »multifix«, 230 V AC, 50 Hz, Size 4, G 3/4, Input pressure 2 - 16 bar, Med. / ambient temp. max. 60°C

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.

3/2-way type including silencer.

When they are switched off, the system is relieved at the same time.

**Tehnične Specifikacije**

|                              |                                                       |
|------------------------------|-------------------------------------------------------|
| Električni priključek        | Device plug PG 9, type B, EN 175301-803               |
| IP zaščita                   | IP65 (P 54) acc. to DIN 40050                         |
| Merjenje pretoka             | At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/4                                                 |
| Odzračevalni vtič            | G 1/2                                                 |
| Ohišje                       | Die-cast aluminium                                    |
| Serijska                     | multifix                                              |
| Tesnilo                      | NBR                                                   |
| Min. vhodni tlak [bar]       | 2                                                     |
| Velikost                     | 4                                                     |
| Max. vhodni tlak [bar]       | 16                                                    |
| E [mm]                       | 35.0                                                  |
| C [mm]                       | 53.0                                                  |
| Max. sobna temperatura [°C]  | 60                                                    |
| Max. temperatura medija [°C] | 60                                                    |
| D [mm]                       | 66.0                                                  |
| A [mm]                       | 85.0                                                  |
| Delovni cikel [%]            | 100                                                   |
| B [mm]                       | 204.0                                                 |
| Solenoid                     | 230 V AC, 50 Hz                                       |
| Pretok [l/min]               | 12500                                                 |