

Datum: 01.05.2025



(slika je simbolična)

## Priključna omarica, vhod G 1/2, priključek 2 x G 1/2

Kategorija: [End distributor without through-hole thread, PN 15](#)

Šifra: **112614RIE**

### Kratek opis

End distributor, Input G 1/2, Connection 2 x G 1/2, operat.pressure (air/water) max. 15 bar, ambient temp. 1 °C to 50 °C

Made of plastic PA6 GF 30.

End and through distributor sockets made of high strength, glass fibre reinforced plastic (PA6 GF 30) with large range of applications.

Optionally 1 or up to 3 connection options as well as 2 thread sizes for internal and external threads (cannot be combined). For vertical carrying of media.

Universal distributor socket with up to 5 connection options. Suitable for vertical and/or horizontal carrying of media or the secure connection

(avoidance of existing components) of pressure reducer or maintenance device, for example.

All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape.

Suitable for media compressed air (ambient temperature -10 °C to 50 °C) or water (ambient temperature 1 °C to 50 °C). Drilling diagram dimensions

are identical for all distributor sockets, so a simpler and more flexible exchange between end, through and universal distributor sockets is ensured.

Caution:

Note that the distributor sockets should not be installed in danger zones. Danger zones are, for example, transport routes, escape routes, etc.

### Tehnične Specifikacije

|                                                 |                                             |
|-------------------------------------------------|---------------------------------------------|
| Dovodni navoj                                   | G 1/2                                       |
| Ohišje                                          | Glass fibre-reinforced plastic<br>PA6 GF 30 |
| Min. temperaturno območje [°C]                  | 1                                           |
| Priključni navoj                                | 2 x G 1/2                                   |
| Max. moment privijanja - pritrdilne luknje [Nm] | 4                                           |
| Max. moment privijanja - medeninasta nit [Nm]   | 12                                          |
| Max. obratovalni tlak [bar]                     | 15                                          |
| Max. temperaturno območje [°C]                  | 50                                          |