

Datum: 30.04.2025



(slika je simbolična)

Priklopne hitre spojke I.D. 5, G 1/4 notranji navoj, zelena

Kategorija: [Non-interchangeable coupling DN 5, female](#)Šifra: **107628RIE**

Kratek opis

Captive quick-connect coupling I.D. 5, Bright brass, G 1/4 IT, green, max. 35 bar, Medium / ambient temp. -20°C to 100°C
One-hand quick disconnect couplings with a large bore.
Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours.
Only couplings and plugs of the same colour fit together.
Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, aerospace.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Barva	Green
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	G 1/4 IT
Pritrdilni obroč	Stainless steel
Sprostitutveni rokav	Anodised aluminium
Tesnilo	NBR
Ventil	Brass with a bare metal surface
Vzmet	Stainless steel
DN	5
a/f [mm]	17
Dolžina [mm]	47.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	560 l/min (air)