

Datum: 01.05.2025



(slika je simbolična)

Proporcionalni kont. ventil »pulstronic II«24V DC, G1/4, DN4

Kategorija: [Proportional control valves, »pulstronic II« type](#)Šifra: **101630RIE**

Kratek opis

Proportional control valve »pulstronic II«, 3-way design, with control circuit, 24 V DC, G 1/4, DN 4, Pressure range 0 - 10 bar

For electronic pressure control

Compact, electropneumatic pressure regulating valve which converts an electronic signal to a pneumatic pressure.

It is particularly suited for precise pressure regulation as well as for pressure control in conjunction with a constant flow due to its internal control loop with electronic pressure feedback.

Operating principle:

Two pulsed pilot valves change the pressure in the control chamber.

A downstream pressure booster converts the pilot pressure into an outlet pressure.

The outlet pressure is measured with a pressure sensor and fed into the internal control loop.

The setpoint is established over the electrical plug-in connector as a standard signal (0 to 10 V).

Tehnične Specifikacije

Delovanje	Pulsed 3/2-way valves
Električna nastavitev	0 - 10 V, 0 - 20 mA, 4 - 20 mA
histereza	< 1% FS
Merjenje pretoka	At P ₂ = 6 bar
Navoj	G 1/4
Notranji deli	POM
Ohišje	POM
Ponovljivost	± 0.5% FS
Poskusno	0 - 10 V
Srednje	Air or neutral gases, filter.50 µm, lubricat. or unlubricat.
Tesnilo	NBR, FPM
Vedenje v varnostnem načinu	Maintenance of press. in case of loss of voltage-non control
DN	4
Max. delovni tlak [bar]	10
B [mm]	46.5
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	60
H [mm]	144.0
Pretok [l/min]	470