

Datum: 29.04.2025



(slika je simbolična)

Ravni potisni fitting »klik klak« M3 o., Cev zunanja Ø 3

Kategorija: [Male connector, parallel male thread with O-ring](#)

Šifra: **108547RIE**

Kratek opis

Straight push-in fitting »click-clock«, M3 o., for hose exterior Ø 3 mm, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.99
a/f [mm]	Ø 5.8
Material	Nickel-plated brass
Navoj	M3
Priporočena cev	PA, PU
Rokav	Nickel-plated brass
Serijska	click-clock
Vpenjalni obroč	Stainless steel
Zunanji šesterokotnik	Without
Šestkotna glava vtičnice [mm]	1.5
Za cevi O.D. [mm]	3
L1 [mm]	12.6
Max. delovni tlak [bar]	16
Max. delovna temperatura [°C]	80