

Datum: 15.12.2025



(slika je simbolična)

## Ravni vtični konekt., rdeča. 8 mm klikni klak

Kategorija: [Reducers with push-in plug](#)

Šifra: **108775RIE**

### Kratek opis

Straight push-in connector, Plug nipple reducing 8 mm, »click-clock«, for hose exterior Ø 5 mm, Working pressure -0.99 to 16 bar

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Only recommended for use in combination with quick-connect fittings of the "click-clock" series.

The suitability test for use with other series is the responsibility of the user.

### Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.99               |
| Material                      | Nickel-plated brass |
| Priporočena cev               | PA, PU              |
| Rokav                         | Hostaform           |
| Serija                        | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| Za cevi O.D. [mm]             | 5                   |
| Priključek [mm]               | 8                   |
| Max. delovni tlak [bar]       | 16                  |
| L1 [mm]                       | 34.5                |
| Max. delovna temperatura [°C] | 80                  |