

Datum: 30.04.2025



(slika je simbolična)

## Ravni vtični konektor z vtičem nastavek 10 mm, zmanjšanje

Kategorija: [Reducers with push-in plug »Stainless steel«](#)

Šifra: **135286RIE**

### Kratek opis

Straight push-in connector with plug nipple 10 mm, reducing, for hose exterior Ø 6 mm, Working pressure -0.98 - 20 bar, 1.4404

For use in more aggressive environments and corrosive media.

Only recommended for use in combination with stainless steel quick connectors type 844 ff. Suitability testing for use with other series is the responsibility of the user.

### Tehnične Specifikacije

|                               |                           |
|-------------------------------|---------------------------|
| Min. delovna temperatura [°C] | -20                       |
| Min. temperatura medija [°C]  | -20                       |
| Min. delovni tlak [bar]       | -0.98                     |
| Material                      | Stainless steel<br>1.4404 |
| Primerni materiali za cevi    | PVDF, PTFE, PA, PU        |
| Za cevi O.D. [mm]             | 6                         |
| Priključek [mm]               | 10                        |
| Max. delovni tlak [bar]       | 20                        |
| L1 [mm]                       | 42.8                      |
| Max. delovna temperatura [°C] | 150                       |
| Max. temperatura medija [°C]  | 150                       |