

Datum: 30.04.2025



(slika je simbolična)

## Red. objemka 270-okroglaN.N./N.N.Rp 3črn

Kategorija: [Socket 270, female/female, black](#)

Šifra: **133726RIE**

### Kratek opis

Bushing 270, IT/IT, Rp 3, black malleable iron fitting,  
Operating temp. -20 °C to 300 °C, ISO 7-1  
According to DIN EN 10242 (previously 2950).  
Malleable iron cast fittings in black steel, non-galvanized, is  
the classic fitting series in connection series in piping  
construction. Our malleable iron cast fittings are  
characterized by high mechanical strength and standardized  
fitting technology.  
Working minimal temperature = -20 °C, 25 bar.  
Working pressure for temperature range from -20 °C to 120  
°C: 25 bar.  
Working pressure for temperature range from 120 °C to 300  
°C: 20-25 bar.

### Tehnične Specifikacije

|                                   |                                                     |
|-----------------------------------|-----------------------------------------------------|
| Min. temperaturno območje<br>[°C] | -20                                                 |
| Material                          | Black malleable iron<br>B350-10, design<br>symbol A |
| Navoj                             | Rp 3                                                |
| Površina                          | Black                                               |
| Standardni navoj                  | acc. ISO 7-1                                        |
| Max. temperaturno območje<br>[°C] | 300                                                 |