

Datum: 15.12.2025

**Serv. enota 2-delna»FUTURA« Kov. Vel.1, G 1/4, 0.1-2 Avt.**

(slika je simbolična)

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)Šifra: **152419RIE****Kratek opis**

Service unit 2-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 1, G 1/4, Control range 0.1-2 bar, Fully

Two-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Element filtra | Cellpor (PE) |
| Membrane | NBR |
| | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Merjenje pretoka | G 1/4 |
| Navoj | Fully-automatic |
| Odtok kondenzata | PA66 GF60 |
| Ohišje | Metal container with viewing tube |
| Posoda | Material: Die-cast zinc |
| Priključni navoj | FUTURA |
| Serijska | Compressed air, neutral gases |
| Srednje | NBR |
| Tesnilo | PC |
| Vidna kupola | 0.1 |
| Min. krmilno območje [bar] | 1 |
| Velikost | 1.5 |
| Min. vhodni tlak [bar] | 2 |
| Max. krmilno območje [bar] | 2.5 |
| Zaslon manometra max. [bar] | 5 |
| Rang filtra [µm] | 16 |
| Max. vhodni tlak [bar] | 50 |
| Max. temperaturno območje [°C] | 96.0 |
| C [mm] | 104.0 |
| A [mm] | 243.0 |
| B [mm] | 1750 |
| Pretok [l/min] | |