

Datum: 15.12.2025



(slika je simbolična)

Serv. enota 2-delna»FUTURA«Kov.Vel.1, G3/8, 0.2-4, Pol avto.Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)Šifra: **152402RIE****Kratek opis**

Service unit 2-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 1, G 3/8, Control range 0.2 - 4 bar, Semi

Two-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 10$ bar, $P_2 = 6.3$
Merjenje pretoka	bar and pressure drop
	$\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vidna kupola	PC
Min. krmilno območje [bar]	0.2
Velikost	1
Min. vhodni tlak [bar]	1.5
Max. krmilno območje [bar]	4
Rang filtra [µm]	5
Zaslon manometra max. [bar]	6
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	96.0
A [mm]	104.0
B [mm]	226.0
Pretok [l/min]	1750