

Datum: 30.04.2025



(slika je simbolična)

Serv. enota 2-delna »FUTURA« Kov. Vel.4, G3/4, 0.1-2 Pol avto.Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)Šifra: **152407RIE****Kratek opis**

Service unit 2-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 4, G 3/4, Control range 0.1 - 2 bar, Semi

Two-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/4
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Poraba zraka	Yes
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vidna kupola	PC
Min. krmilno območje [bar]	0.1
Max. notranja poraba zraka	1.5 l/min (depending on secondary pressure)
Min. vhodni tlak [bar]	1.5
Max. krmilno območje [bar]	2
Zaslon manometra max. [bar]	2.5
Velikost	4
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	137.0
A [mm]	170.0
B [mm]	326.0
Pretok [l/min]	12000