

Datum: 30.04.2025



(slika je simbolična)

Serv. enota 2-delna »GA-mali« 5 µm, Vel.200, G1/4, 1.5 - 9 bar

Kategorija: [Service units 2-piece](#)

Šifra: **178362RIE**

Kratek opis

Service unit 2-part »GA-mini«, with PC container, 5 µm, Size 200, G 1/4, Input pressure max. 10 bar, Control range 1.5 - 9 bar

Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast aluminium
Serijska	GA-mini
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
Max. temperaturno območje [°C]	70
C [mm]	73.0
D [mm]	98.0
A [mm]	108.0
B [mm]	171.0
Velikost	200
Pretok [l/min]	900