

Datum: 16.12.2025



(slika je simbolična)

Serv. enota 2-delna »Stinard« z PC zbir.Vel.1,G 1/4

Kategorija: [Service unit, 2-piece with polycarbonate bowl](#)Šifra: **101046RIE**

Kratek opis

Service unit 2-part »Standard« with polycarbonate container, Size 1, G 1/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc / aluminium, painted silver
Posoda	Polycarbonate container
Serijska	Standard
Tesnilo	NBR
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost	1
Rang filtra [μ m]	5
DN	6
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	16
Manometer $\varnothing$ [mm]	50
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	106.5
A [mm]	117.0
B [mm]	236.2
Pretok [l/min]	600