

Datum: 30.04.2025



(slika je simbolična)

Serv. enota 2-delna »Stinard« z PC zbir.Vel.4,G 3/4

Kategorija: [Service unit, 2-piece with polycarbonate bowl](#)Šifra: **101050RIE**

Kratek opis

Service unit 2-part »Standard« with polycarbonate container, Size 4, G 3/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p =$ 1 bar
Navoj	G 3/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc / aluminium, painted silver
Posoda	Polycarbonate container
Serijska	Standard
Tesnilo	NBR
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost	4
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
DN	20
Rang filtra [μ m]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Manometer Ø [mm]	63
C [mm]	190.6
A [mm]	220.0
B [mm]	452.0
Pretok [l/min]	4000