

Datum: 30.04.2025



(slika je simbolična)

**Serv. enota 3-delna »FUTURA« PC, Vel. 4, G 1, 0.2-4 Avt.**Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)Šifra: **152660RIE****Kratek opis**

Service unit 3-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 4, G 1, Control range 0.2 - 4 bar, Fully

Three-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

**Tehnične Specifikacije**

|                                |                                                                         |
|--------------------------------|-------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                     |
| Element filtra                 | Cellpor (PE)                                                            |
| Membrane                       | NBR                                                                     |
| Merjenje pretoka               | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                          | G 1                                                                     |
| Odtok kondenzata               | Fully-automatic                                                         |
| Ohišje                         | PA66 GF60                                                               |
| Poraba zraka                   | Yes                                                                     |
| Posoda                         | Polycarbonate container with protective cage                            |
| Priključni navoj               | Material: Die-cast zinc                                                 |
| Serijska                       | FUTURA                                                                  |
| Srednje                        | Compressed air, neutral gases                                           |
| Tesnilo                        | NBR                                                                     |
| Vidna kupola                   | PC                                                                      |
| Min. krmilno območje [bar]     | 0.2                                                                     |
| Max. notranja poraba zraka     | 1.5 l/min (depending on secondary pressure)                             |
| Min. vhodni tlak [bar]         | 1.5                                                                     |
| Max. krmilno območje [bar]     | 4                                                                       |
| Velikost                       | 4                                                                       |
| Rang filtra [µm]               | 5                                                                       |
| Zaslon manometra max. [bar]    | 6                                                                       |
| Max. vhodni tlak [bar]         | 16                                                                      |
| Max. temperaturno območje [°C] | 50                                                                      |
| C [mm]                         | 137.0                                                                   |
| A [mm]                         | 255.0                                                                   |
| B [mm]                         | 343.0                                                                   |
| Pretok [l/min]                 | 12000                                                                   |