

Datum: 14.12.2025



(slika je simbolična)

Serv. enota 3-delna »multifix«Kov. pos.Vel.1,G 3/8

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)Šifra: **100592RIE**

Kratek opis

Service unit 3-part »multifix«, Metal container, Viewing tube, Size 1, G 3/8, Input pressure max. 20 bar, Control range 0.5-10 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Posoda	Metal container with viewing tube
Serija	multifix
Tesnilo	NBR
Vidna kupola	Zinc-glass-NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
Velikost	1
Rang filtra [μ m]	5
DN	10
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	16
Max. vhodni tlak [bar]	20
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	67.0
D [mm]	125.5
A [mm]	137.8
B [mm]	192.5
Pretok [l/min]	1200