

Datum: 16.12.2025



(slika je simbolična)

## Serv. enota 3-delna »Stinard« z PC zbir.Vel. 3G 1/2

Kategorija: [Service unit, 3-piece with polycarbonate bowl](#)Šifra: **101067RIE**

### Kratek opis

Service unit 3-part »Standard« with polycarbonate container, Size 3, G 1/2, Input pressure max. 16 bar, Control range 0.5 - 10 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/2                                                                |
| Odtok kondenzata             | Semi-automatic                                                       |
| Ohišje                       | Die-cast zinc / aluminium, painted silver                            |
| Posoda                       | Polycarbonate container                                              |
| Serijska                     | Standard                                                             |
| Tesnilo                      | NBR                                                                  |
| Vidna kupola                 | PA                                                                   |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 3                                                                    |
| Rang filtra [ $\mu$ m]       | 5                                                                    |
| Max. krmilno območje [bar]   | 10                                                                   |
| DN                           | 15                                                                   |
| Max. vhodni tlak [bar]       | 16                                                                   |
| Zaslona manometra max. [bar] | 16                                                                   |
| C [mm]                       | 55.0                                                                 |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| Manometer Ø [mm]             | 63                                                                   |
| B [mm]                       | 223.4                                                                |
| A [mm]                       | 259.0                                                                |
| Pretok [l/min]               | 3200                                                                 |