

Datum: 29.04.2025



(slika je simbolična)

## Servisna enota 3-delna »multifix-mali«, Kovinska posoda, G 1/4

Kategorija: [Service unit, 3-piece with metal bowl](#)

Šifra: **100401RIE**

### Kratek opis

Service unit 3-part »multifix-mini« with metal container, Size 0, G 1/4, Input pressure max. 12 bar, Control range 0.5 - 10 bar

Three-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1/4                                                                   |
| Odtok kondenzata             | Semi-automatic                                                          |
| Ohišje                       | Die-cast zinc                                                           |
| Posoda                       | Metal container                                                         |
| Serijska                     | multifix-mini                                                           |
| Tesnilo                      | NBR                                                                     |
| Vidna kupola                 | Zinc-glass-NBR                                                          |
| Vzmet pokrova motorja        | POM-brass                                                               |
| Min. krmilno območje [bar]   | 0.5                                                                     |
| DN                           | 5                                                                       |
| Rang filtra [ $\mu$ m]       | 5                                                                       |
| Max. krmilno območje [bar]   | 10                                                                      |
| Max. vhodni tlak [bar]       | 12                                                                      |
| Zaslona manometra max. [bar] | 16                                                                      |
| Max. sobna temperatura [°C]  | 60                                                                      |
| Max. temperatura medija [°C] | 60                                                                      |
| C [mm]                       | 63.0                                                                    |
| D [mm]                       | 99.3                                                                    |
| A [mm]                       | 120.0                                                                   |
| B [mm]                       | 162.3                                                                   |
| Pretok [l/min]               | 750                                                                     |