

Datum: 29.04.2025



(slika je simbolična)

Servisna enota 3-delna »Stinard-mali« s kovinsko posodo, G 1/8

Kategorija: [Service unit, 3-piece with metal bowl](#)

Šifra: **100803RIE**

Kratek opis

Service unit 3-part »Standard-mini«, Metal container, pressure gauge, G 1/8, Input pressure max. 25 bar, Control range 0.5-10 bar

Compact, three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/8
Odtok kondenzata	Manual
Ohišje	Die-cast zinc, painted silver
Posoda	Metal container
Serijska	Standard-mini
Tesnilo	NBR
Vidna kupola	Zinc-glass-NBR
Min. krmilno območje [bar]	0.5
DN	5
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	16
Max. vhodni tlak [bar]	25
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	70.2
D [mm]	98.5
A [mm]	130.0
B [mm]	168.7
Pretok [l/min]	300