

Datum: 16.12.2025

**Servisna enota VARNOSTNA »FUTURA«, Velikost 1, G 3/8**

(slika je simbolična)

Kategorija: [SAFETY service unit set](#)Šifra: **100268RIE****Kratek opis**

Service station SAFETY »FUTURA«, Ball valve - start-up valve
- 2-part service unit, Size 1, G 3/8, Input pressure 2.5 - 16
bar

These compressed air service unit sets, comprising a ball
valve with silencer, a start-up valve and one out of a
pressure regulator, filter regulator or service unit, meet
even the strictest requirements for operating reliability and
accident prevention!

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 10$ bar, $P_2 = 6.3$
Merjenje pretoka	bar and pressure drop
	$\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Odzračevalni vtič	Silencer (ball valve)
Ohišje	PA66 GF60
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral
	gases
Tesnilo	NBR
Velikost	1
Min. krmilno območje [bar]	2.5
Min. vhodni tlak [bar]	2.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	8
Zaslon manometra max. [bar]	10
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	96.0
A [mm]	208.0
B [mm]	243.0
Pretok [l/min]	1750