

Datum: 16.12.2025

**Servisna enota VARNOSTNA »FUTURA«, Velikost 4, G 3/4**

(slika je simbolična)

Kategorija: [SAFETY service unit set](#)Šifra: **100247RIE****Kratek opis**

Service station SAFETY »FUTURA«, Ball valve - start-up valve - pressure regulator, Size 4, G 3/4, Input pressure 2.5 - 16 bar

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/4
Odzračevalni vtič	Silencer (ball valve)
Ohišje	PA66 GF60
Poraba zraka	Yes
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Max. notranja poraba zraka	1.5 l/min (depending on secondary pressure)
Min. krmilno območje [bar]	2.5
Min. vhodni tlak [bar]	2.5
Velikost	4
Rang filtra [µm]	5
Max. krmilno območje [bar]	8
Zaslona manometra max. [bar]	10
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	137.0
B [mm]	191.0
A [mm]	255.0
Pretok [l/min]	10000