

Datum: 17.12.2025



(slika je simbolična)

stand. cilinderdelujoč v dveh smerehbat Ø 100, hod 450, G1/2

Kategorija: [Standard cylinders »SAI« Series](#)

Šifra: **170684RIE**

Kratek opis

Standard cylinder SAI, ISO 15552, double-acting, Piston Ø 100, Stroke 450, G 1/2, Working pressure 1.5-10 bar, Temp. -20°C to 70°C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning.

The magnetic switches are mounted in T-slots on two sides of the body.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel, thick-chromed
Cushioning	cushioned
ET batnice	M20x1.5
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Aluminium jacket with integrated T-slots
Povezava	G 1/2
Standard	acc. to ISO 15552
Tesnilo	NBR (O-rings)
Tesnilo batnice	TPU (thermoplastic polyurethane)
Min. delovni tlak [bar]	1.5
Max. delovni tlak [bar]	10
Batnica Ø [mm]	25
Max. temperaturno območje [°C]	70
Bat Ø [mm]	100
Stroke [mm]	450