

Datum: 01.05.2025



[stand. cilindrdelujoč v dveh smerehbat Ø 125hod 600G 1/2](#)

(slika je simbolična)

Kategorija: [Standard cylinders - AirSentials](#)Šifra: **114632RIE**

Kratek opis

Standard cylinder »SE« ISO 15552, double-acting, Piston Ø 125, Stroke 600, G 1/2, Working pressure 1 - 10 bar, Temp. -20°C to 70°C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning. The magnetic switches are mounted in T-slots on three sides of the body.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel, thick-chromed
Cushioning	cushioned
ET batnice	M27x2
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod with magnet
Magnet	Aluminium jacket with integrated T-slots
Ovoj	G 1/2
Povezava	SE series
Serija	acc. to ISO 15552
Standard	NBR (O-rings)
Tesnilo	TPU (thermoplastic polyurethane)
Tesnilo batnice	1
Min. delovni tlak [bar]	10
Max. delovni tlak [bar]	32
Batnica Ø [mm]	70
Max. temperaturno območje [°C]	125
Bat Ø [mm]	600
Stroke [mm]	