

Datum: 30.04.2025



(slika je simbolična)

**stand. cilindodelujoč v dveh smerehbat Ø 50hod 25G 1/4**Kategorija: [Standard cylinders](#)Šifra: **106204RIE****Kratek opis**

Standard cylinder, ISO 15552, double-acting, Piston Ø 50, Stroke 25, G 1/4, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning.

The magnetic switches can be mounted in two T-slots on the same side as the compressed air supply.

The version with a 125 mm bore is provided with fixing accessories on three sides as standard.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

**Tehnične Specifikacije**

|                                |                                                               |
|--------------------------------|---------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                           |
| Bat                            | POM                                                           |
| Batnica                        | C45 steel, hard chrome-plated                                 |
| Cushioning                     | cushioned                                                     |
| ET batnice                     | M16x1.5                                                       |
| Ffunkcija                      | double-acting                                                 |
| Gewinde Kolbenstange           | male piston rod                                               |
| Magnet                         | with magnet                                                   |
| Navoj na batnici               | M16x1.5                                                       |
| Oblika                         | Heads / jacket with self-tapping screws<br>Anodised aluminium |
| Ovoj                           | jacket with integrated T-slots                                |
| Povezava                       | G 1/4                                                         |
| Standard                       | acc. to ISO 15552                                             |
| Tesnilo                        | NBR                                                           |
| Min. nastavljeni tlak [bar]    | 0.3                                                           |
| Max. delovni tlak [bar]        | 10                                                            |
| Batnica Ø [mm]                 | 20                                                            |
| Stroke [mm]                    | 25                                                            |
| Bat Ø [mm]                     | 50                                                            |
| Max. temperaturno območje [°C] | 80                                                            |