

Datum: 30.04.2025



(slika je simbolična)

## Standardni manometer, CrNi jeklo, G 1/4, 0 - 60 bar, Ø 50

Kategorija: [Pressure gauge CrNi steel, standard, radial bottom](#)

Šifra: **102426RIE**

### Kratek opis

Standard pressure gauge CrNi steel design, Connection radial bottom, G 1/4, Goods class 2.5, Measurement range 0 - 60 bar, Ø 50

Bourdon-tube pressure gauge (standard model) manufactured entirely from CrNi steel, economical and reliable.

Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere. Clean dry air applications, machinery and industrial plant engineering in general.

### Tehnične Specifikacije

|                                            |                  |
|--------------------------------------------|------------------|
| Min. sobna temperatura [°C]                | -40              |
| Min. temperatura medija [°C]               | -40              |
| Material                                   | CrNi steel       |
| Material Prozessanschluss                  | CrNi steel       |
| Položaj povezave                           | radial on bottom |
| Povezava                                   | G 1/4            |
| Prednje steklo                             | Polycarbonate    |
| Razred točnosti                            | 2.5              |
| Stopnja rasti na območju skale - bar [bar] | 5                |
| Premer [mm]                                | 50               |
| Max. sobna temperatura [°C]                | 60               |
| Merilno območje max. bar                   | 60               |
| Max. temperatura medija [°C]               | 100              |
| Vrsta                                      | 131.11           |
| Merilno območje max. psi                   | 860              |