

Datum: 30.04.2025



(slika je simbolična)

Standardni manometer, priklp spodaj, G 1/2, 0 - 0.6 bar, Ø 100

Kategorija: [Standard pressure gauge, conn. radial on bottom](#)

Šifra: **101968RIE**

Kratek opis

Standard pressure gauge, Single scale bar, Connection radial bottom, G 1/2, Goods class 1.6, Measurement range 0 - 0.6 bar, Ø 100

Bourdon-tube pressure gauge in standard design.
Suitable for gaseous or liquid media which do not corrode copper alloy,
do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Plastic
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Transparent plastic
Premikanje	Copper alloy
Referenčni kazalnik	red
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.01
Merilno območje max. bar	0.6
Razred točnosti	1.6
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premier [mm]	100
Vrsta	111.10