

Datum: 29.04.2025



(slika je simbolična)

Stenski priključek z varnostno tipko I.D. 7.4

Kategorija: [Distributor socket with pushbutton-type safety coupling](#)Šifra: **107579RIE**

Kratek opis

End distributor socket, 3 safety couplings I.D. 7.4, input G3/4, Op. pressure max. 12 bar, temp. air -10°C to 50°C, temp. water 1°C to 50°C
2 or 3-way distributor sockets made of high-strength glass fibre-reinforced plastic (PA6 GF 30) for a wide range of applications. All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange replacement. Caution: Note that the distributor sockets should not be installed in danger zones. Danger zones are, for example, transport routes, escape routes, etc.

Tehnične Specifikacije

Min. delovna temperatura v zraku [°C]	-10
Dovodni navoj	G 3/4
Material navojev	Brass
Ohišje	Glass fibre-reinforced plastic PA6 GF 30
Min. delovna temperatura v vodi [°C]	1
Spojka	3 x Safety coupling
Max. moment privijanja - pritrdilne luknje [Nm]	4
Max. moment privijanja - medeninasta nit [Nm]	12
Max. obratovalni tlak [bar]	12
Max. delovna temperatura v vodi [°C]	50
Max. delovna temperatura v zraku [°C]	50
Višina [mm]	59.0
Premer [mm]	156.0