

Datum: 30.04.2025



(slika je simbolična)

Temperaturna sklopka DN 9Z.N.zaporni ventil,Med.G 3/8 90°

Kategorija: [Temp. control coupl. DN 9, ET, with shut-off valve](#)

Šifra: **107964RIE**

Kratek opis

Tempered coupling DN 9, Exterior thread, Blocking valve, Brass, G 3/8 90°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C
Compatible with HASCO Z 8 system.
For temperature control applications involving hot or cold water or heat transfer oil.
Optionally with free passage, one or both sides sealing.
Female-threaded couplings and plugs with female-threaded PTFE seal.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Priključni navoj	G 3/8 90°
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
Max. obratovalni tlak [bar]	15
a/f [mm]	22
Dolžina [mm]	54.0
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160