

Datum: 01.05.2025



(slika je simbolična)

Tlačni pretvornik, 0 - 25 bar, G 1/2, CrNi jeklo1.4571

Kategorija: [Pressure transmitter \(CrNi steel 1.4571\), S-10](#)

Šifra: **102701RIE**

Kratek opis

Pressure transducer for general industrial applications, Non-linearity 0.2%, Measurement range 0-25 bar, G 1/2, CrNi steel 1.4571

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

Tehnične Specifikacije

Min. temperatura medija [°C]	-30
Min. sobna temperatura [°C]	-20
Deli v kontaktu z medijem	CrNi steel 1.4571
Električni priključek	With right-angle connector acc. to DIN EN 175301-803 A
IP zaščita	IP 65 acc. to EN 60529
Navoj	G 1/2
Ohišje	CrNi steel 1.4571
Operativna napetost	DC 10 ... 30 V
Spodnja/Zgornja meja območja	Positive pressure
Vrsta	S-10
Nelinearnost	0.2% of span
izhodni signal	4 - 20 mA, 2-wire
Merilno območje max. bar	25
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	100