

Datum: 17.12.2025



(slika je simbolična)

## Tlačni reg. za panelno montažo »Stinard«Vel. 1, G1/4, 0.5-6

Kategorija: [Pressure regulators for panel mounting](#)

Šifra: **100850RIE**

### Kratek opis

Pressure regulator for control panel integration »Standard«, without pressure gauge, Size 1, G 1/4, max. 16 bar, 0.5 - 6 bar

Incl. panel nut and washer.

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1/4                                                                |
| Navoj za pritrditev plošče   | M20x1.5                                                              |
| Ohišje                       | Die-cast zinc, painted silver                                        |
| Serijska                     | Standard                                                             |
| Tesnilo                      | NBR                                                                  |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 1                                                                    |
| DN                           | 6                                                                    |
| Max. krmilno območje [bar]   | 6                                                                    |
| Max. vhodni tlak [bar]       | 16                                                                   |
| C [mm]                       | 32.0                                                                 |
| A [mm]                       | 54.0                                                                 |
| Max. temperatura medija [°C] | 60                                                                   |
| Max. sobna temperatura [°C]  | 80                                                                   |
| D [mm]                       | 97.5                                                                 |
| Pretok [l/min]               | 1000                                                                 |