

Datum: 30.04.2025



(slika je simbolična)

## Tlačni regulator iz nerjevečega jekla, 1.4404, G 1/4, 1 - 15 bar

Kategorija: [Non-reversible, stainless steel pressure regulator](#)

Šifra: **101196RIE**

### Kratek opis

Stainless steel pressure regulator, 1.4404, without secondary venting (non-reversible), G 1/4, Control range 1 - 15 bar

Stainless steel regulators containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

### Tehnične Specifikacije

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Membrane                     | PTFE on NBR-carrier                                                     |
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p \leq 1$ bar |
| Navoj                        | G 1/4                                                                   |
| Ohišje                       | Stainless steel 1.4404 (AISI 316L)                                      |
| Tesnilo                      | FKM                                                                     |
| Min. krmilno območje [bar]   | 1                                                                       |
| Max. krmilno območje [bar]   | 15                                                                      |
| C [mm]                       | 37.0                                                                    |
| Max. vhodni tlak [bar]       | 50                                                                      |
| A [mm]                       | 64.0                                                                    |
| Max. sobna temperatura [°C]  | 80                                                                      |
| Max. temperatura medija [°C] | 80                                                                      |
| D [mm]                       | 122.0                                                                   |
| B [mm]                       | 160.0                                                                   |
| Pretok [l/min]               | 1300                                                                    |