

Datum: 30.04.2025



(slika je simbolična)

Tlačni regulator iz nerjevečega jekla, G 3/8, 0.4 - 4.0 bar

Kategorija: [Stainless steel casting pressure regulators 1.4401](#)

Šifra: **137325RIE**

Kratek opis

Stainless steel casting pressure regulator, 1.4401, secondary venting (reversible), Size 1, G 3/8, Control range 0.4 - 4.0 bar

Stainless steel regulators for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc. Pressure setting by T-handle.

Tehnične Specifikacije

Membrane	NBR/PTFE
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p \leq 1$ bar
Navoj	G 3/8
Ohišje	Stainless steel casting 1.4401 (AISI 316)
Tesnilo	NBR
Min. krmilno območje [bar]	0.4
Velikost	1
Max. krmilno območje [bar]	4
Max. vhodni tlak [bar]	30
C [mm]	51.0
A [mm]	62.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
D [mm]	115.0
B [mm]	166.0
Pretok [l/min]	3965