

Datum: 01.05.2025



(slika je simbolična)

## Varn. ventil, med., G 3/4, vkl. prit. 9.5 bar

Kategorija: [Varnostni ventil G 3/4](#)

Šifra: **104890RIE**

### Kratek opis

Safety valve, High performance design, Brass, Operating temp. -40 °C to 200 °C, G 3/4, AF 32, Trigger pressure 9.5 bar

For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

These valves are TÜV approved and have a TÜV type test number.

### Tehnične Specifikacije

|                               |         |
|-------------------------------|---------|
| Min. delovna temperatura [°C] | -40     |
| Navoj                         | G 3/4   |
| Ohišje                        | Brass   |
| Tesnilo                       | FPM     |
| Tlačna vzmet                  | C steel |
| Min. obratovalni tlak [bar]   | 0.5     |
| Min. nastavljeni tlak [bar]   | 9.5     |
| narediti [mm]                 | 15.0    |
| A [mm]                        | 16.0    |
| Max. obratovalni tlak [bar]   | 26      |
| a/f [mm]                      | 32      |
| H [mm]                        | 110.0   |
| Max. delovna temperatura [°C] | 200     |