

Datum: 15.12.2025



(slika je simbolična)

## Varn.ventil s pol. hod. DN 10, G 3/8, vkl. prit. 21 bar

Kategorija: [Varnostni ventil G 3/8](#)

Šifra: **104490RIE**

### Kratek opis

Full stroke safety valve DN 10, Brass, Operating temp. -25 °C to 180 °C, G 3/8, AF 27, Trigger pressure 21 bar, Type tested

For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

These valves are TÜV approved and have a TÜV type test number.

### Tehnične Specifikacije

|                               |                 |
|-------------------------------|-----------------|
| Min. delovna temperatura [°C] | -25             |
| Navoj                         | G 3/8           |
| Ohišje                        | Brass           |
| Tesnilo                       | FKM             |
| Tlačna vzmet                  | Stainless steel |
| Min. obratovalni tlak [bar]   | 0.2             |
| D [mm]                        | 12.0            |
| Min. nastavljeni tlak [bar]   | 21              |
| A [mm]                        | 22.0            |
| a/f [mm]                      | 27              |
| Max. obratovalni tlak [bar]   | 50              |
| C [mm]                        | 95.0            |
| Max. delovna temperatura [°C] | 180             |