

Datum: 15.12.2025



(slika je simbolična)

## Varnostna čeljustna spojka z notranjim navojem, G 1, DN 17

Kategorija: [Safety claw coupling, female threaded](#)

Šifra: **107882RIE**

### Kratek opis

Safety jaw coupling with interior thread, G 1, DN 17,  
Malleable cast iron, Operating pressure max. 16 bar, Temp.  
-40 °C to 95 °C

Universal standard coupling in safety design according to  
DIN 3238 for absolutely secure compressed air lines on  
construction sites or in industry.

Easy to couple, secured against accidental opening: just  
screw the ring tight after coupling!

- Robust couplings with malleable iron head, steel stem with  
special profile,

zinc plated and yellow chromated

- Chrome VI-free, with double safety lock

- Large bore for increased flow rate

### Tehnične Specifikacije

|                               |                |
|-------------------------------|----------------|
| Min. delovna temperatura [°C] | -40            |
| Material                      | Malleable iron |
| Navoj                         | G 1            |
| Tesnilo                       | NBR            |
| Max. obratovalni tlak [bar]   | 16             |
| DN                            | 17             |
| a/f [mm]                      | 41             |
| Razdalja med objemkami [mm]   | 42             |
| H [mm]                        | 63.0           |
| L [mm]                        | 92.2           |
| Max. delovna temperatura [°C] | 95             |