

Datum: 29.04.2025



(slika je simbolična)

## Visoko zmogl. varnos.ventil, G 1 1/2, vkl. prit. 8.5 bar

Kategorija: [High-pressure Varnostni ventil G 1 1/2](#)

Šifra: **105361RIE**

### Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260°C, G 1 1/2, AF 60, Trigger pressure 8.5 bar

Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.

Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).

Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

### Tehnične Specifikacije

|                               |                                    |
|-------------------------------|------------------------------------|
| Navoj                         | G 1 1/2                            |
| Ohišje                        | Brass                              |
| Vzmet pokrova motorja         | Malleable iron, powder-coated blue |
| Min. obratovalni tlak [bar]   | 0.5                                |
| Min. nastavljeni tlak [bar]   | 8.5                                |
| A [mm]                        | 20.0                               |
| Max. obratovalni tlak [bar]   | 30                                 |
| narediti [mm]                 | 32.0                               |
| a/f [mm]                      | 60                                 |
| Max. delovna temperatura [°C] | 260                                |
| H [mm]                        | 293.0                              |