

Datum: 01.05.2025



(slika je simbolična)

## Visoko zmogl. varnos.ventil, G 1/2, vkl. prit. 11.5 bar

Kategorija: [High-pressure Varnostni ventil G 1/2](#)

Šifra: **105127RIE**

### Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 1/2, AF 27, Trigger pressure 11.5 bar

Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.

Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).

Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

### Tehnične Specifikacije

|                               |       |
|-------------------------------|-------|
| Navoj                         | G 1/2 |
| Ohišje                        | Brass |
| Vzmet pokrova motorja         | Brass |
| Min. obratovalni tlak [bar]   | 0.5   |
| narediti [mm]                 | 10.0  |
| Min. nastavljeni tlak [bar]   | 11.5  |
| A [mm]                        | 12.0  |
| a/f [mm]                      | 27    |
| Max. obratovalni tlak [bar]   | 30    |
| H [mm]                        | 138.0 |
| Max. delovna temperatura [°C] | 260   |