

Datum: 30.04.2025

Davčna št.: SI 56119488

Telefon: 01 500 14 42

E-mail: info@podjetje-trg.si

WWW: www.karchertest.staging.digitalist.si



(slika je simbolična)

Visoko zmogl. varnos.ventil, G 2, vkl. prit. 1.6 bar

Kategorija: [High-pressure Varnostni ventil G 2](#)

Šifra: **105384RIE**

Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 2, AF 80, Trigger pressure 1.6 bar
Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.
Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).
Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

Tehnične Specifikacije

Navoj	G 2
Ohišje	Brass
Vzmet pokrova motorja	Malleable iron, powder-coated blue
Min. obratovalni tlak [bar]	0.5
Min. nastavljeni tlak [bar]	1.6
A [mm]	22.0
Max. obratovalni tlak [bar]	30
narediti [mm]	40.0
a/f [mm]	80
Max. delovna temperatura [°C]	260
H [mm]	367.0