

Datum: 29.04.2025



(slika je simbolična)

## Visoko zmogljiv tlačni regulator, G 1 1/2, 0.1 - 3 bar

Kategorija: [Heavy-duty pressure regulators](#)Šifra: **101259RIE**

### Kratek opis

High performance pressure regulator with 2 pressure gauges, G 1 1/2, Control range 0.1 - 3 bar, Input pressure max. 25 bar  
Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving design for very high flow rates.  
Separate indication of input and working pressure on two pressure gauges.  
The pressure setting can be locked by pushing the knob down.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1 1/2                                                              |
| Ohišje                       | Aluminium, painted silver                                            |
| Tesnilo                      | NBR                                                                  |
| Min. krmilno območje [bar]   | 0.1                                                                  |
| Max. krmilno območje [bar]   | 3                                                                    |
| Zaslon manometra max. [bar]  | 4                                                                    |
| Max. vhodni tlak [bar]       | 25                                                                   |
| DN                           | 50                                                                   |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| A [mm]                       | 188.0                                                                |
| B [mm]                       | 261.0                                                                |
| Pretok                       | 50000 l/min                                                          |